

SHEETROCK™ Lay-In Ceiling Panel *ClimaPlus*™

10
Year Availability
3270



SHEETROCK Lay-In Ceiling Panel, Vinyl, with *CLIMAPLUS* Performance/
DONN ZXLA Suspension System

Features and Benefits

- CLEAN ROOM™ panels have a vinyl-laminated face with sealed back and edges for use in clean room environments up to Class 100.
- Washable and scrubbable finish—impact and scratch resistant.
- USDA Certified Biobased Product?
- Panels meet USDA/FSIS requirements for food processing areas.
- *CLIMAPLUS*™ 30-year lifetime system warranty against visible sag.

Applications

- Kitchens and food preparation areas
- Restrooms and utility areas
- Locker rooms
- Parking garages
- Exterior protected soffits

Substrate

- Gypsum panel

See LEED report tool at usgdesignstudio.com
for detailed sustainability information.

To order samples, go to usg.com



Flat White
050

Smooth-Textured Panel – Vinyl (PVC)



SHEETROCK™ Lay-In Ceiling Panel *ClimaPlus™*

To order samples/literature:
 Web: usg.com
 E-mail: samplit@usg.com
 Fax: 888.874.2348
 Technical Services:
 800 USG.4YOU (800.874.4968)

Websites:
usg.com
usgdesignstudio.com
 For the most up-to-date technical information:
usgdesignstudio.com

30

Year System Warranty
 – No visible sag

	Edge	Panel Size	Class ²	Item No.	NRC ³	CAC Min.	LR ⁴	Color	Abuse-Resistant	Grid Options	VOC Emissions	Recycled Content ¹	Panel Cost
SHEETROCK™ Lay-In Ceiling Panel <i>CLIMAPLUS™</i> Vinyl	SQ	2'x2'x1/2"		3260	–	35	.77	White		A, B, C, D	Low	40%	\$
		2'x4'x1/2"		3270	–	40	.77	White		A, B, C, D	Low	40%	\$
SHEETROCK Lay-In Ceiling Panel <i>CLIMAPLUS™</i> , CLEAN ROOM™ ⁵	SQ	2'x4'x1/2"		3200	–	40	.77	White		A, B, C, D	Low	40%	\$\$

Legend

Low Emissions (VOC)
 Low-emitting performance meets CA Specification 01350 (CA Dept. of Health Services Standard Practice for the testing of VOC emissions) and is listed on the CHPS database for low-emitting materials. USG Certificate of Compliance for Low VOC Emissions also available on usg.com.

≥ 38 CAC

FIRECODE®

A	B	C	D
DX®/DXL™	DXLA™	ZXLA™	CE™ ⁶

Grid Profile Options

Physical Data/ Footnotes

Product literature
 Data sheet: SC1820

ASTM E1264 classification
 Type XX, Pattern G

ASTM E84 surface burning characteristics

Class A
 Vinyl
 Flame spread: 25
 Smoke developed: 50
 CLEAN ROOM
 Flame spread: 25
 Smoke developed: 50

Weight
 1/2" = 2.00 lbs./sq. ft.

Thermal resistance
 1/2" = R-0.45

Maximum backloading
 See USG 30-Year Limited Warranty Commercial Applications SC2102.

Maintenance
 Can be cleaned easily with a damp sponge. Use mild detergent and water—do not use acetate, ammonia or high concentration of chlorine, bromide or other harsh chemicals.

Application considerations
 Product is directional. Install with all manufactured edges parallel and in the same direction.

U.S. Coast Guard acceptance
 Approved for use on merchant ships

Notes

- For details, see LEED report tool at usgdesignstudio.com.
- Fire-rated items: see UL design details.
- NRC rating is .10. USG does not consider a ceiling panel to be acoustically rated if NRC is less than .50.
- LR values are shown as averages.
- Field-cut edges of CLEAN ROOM panels must be sealed with white latex paint.
- Clean-room-rated applications require a suspension system with gasketed tee flanges such as Donn® CE.
- This product has achieved both BioPreferred initiatives: Federal Procurement Preference and Certified Product Labeling. See the complete listing of all USG ceiling panels on biopreferred.gov website.



Manufactured by USG Interiors, LLC
 550 West Adams Street
 Chicago, IL 60661

The following are trademarks of USG Interiors, LLC or a related company: CE, CLEAN ROOM, CLIMAPLUS, DONN, DX, DXL, DXLA, FIRECODE, SHEETROCK, USG, ZXLA.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read MSDS and literature before specification and installation.

SC1820/rev. 4-13
 © 2013 USG Interiors, LLC
 Printed in U.S.A.