# **PERFORMA®**

# VOC Compliant Symphony® f







#### LEED®

- ✓ Optimize Energy Performance
- ✓ Building Reuse
- ✔ Construction Waste Management
- ✔ Recycled Content
- ✔ Regional Materials
- ✓ Daylight and Views
- ✓ Acoustic Performance

#### **RECYCLED CONTENT**

0% Pre-consumer 29-34%

# **RELATIVE INSTALLED COST: \$\$\$\$**

# **FEATURES & BENEFITS**

- Superior sound absorption (NRC 0.80-0.95)
- Exceeds FGI Guidelines for cleanability and acoustic performance
- Surface washability exceeds 1000 cycles with sanitizing chemicals
- Suitable clean room component to ISO Class 4
- Overtone® finish features extremely high light reflectance (LR 0.90)
- Perfect for enhanced speech privacy and exceptional productivity in open plan environment
- Third-party verified Environmental Product Declaration (EPD) available for this product
- Moisture resistant
- Mix with other Overtone finish products Symphony® m and g, for Fine Tuning possibilities

#### **APPLICATIONS**

- Open Plan Areas - Waiting Rooms - Libraries

- Offices - Nurses Stations - Computer Rooms

## **AVAILABLE EDGE DETAILS**









# ATTRIBUTES - IMPERIAL SIZES

ITEM NUMBER	DIMENSIONS (INCHES)	EDGE DETAIL	NRC	CAC	SAG RESISTANT	MOLD RESISTANT	LR	WASHABLE	SCRATCH RESISTANT	FIRE RATING	LOW VOC EMISSIONS	RECYCLED CONTENT
1322-IOF-1	24 x 24 x 3/4	Trim	0.90	22	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	34%
1320-IOF-1	24 × 48 × 3/4	Trim	0.90	24	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	34%
1342-IOF-1	24 x 24 x 1	Trim Reveal Narrow Reveal	0.95	24	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	36% 38% 38%
1340-IOF-1	24 × 48 × 1	Trim Reveal Narrow Reveal	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	36% 38% 38%
1341-IOF-1	24 x 60 x 1	Trim Reveal Narrow Reveal	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	36% 38% 38%
1358-IOF-1	24 x 72 x 1	Trim	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	36%
1346-IOF-1	24 x 96 x 1	Trim	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	36%
1347-IOF-1	20 × 60 × 1	Trim Reveal Narrow Reveal	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	36% 38% 38%
1343-IOF-1	30 × 30 × 1	Trim Reveal Narrow Reveal	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	36% 38% 38%
1349-IOF-1	30 × 60 × 1	Trim Reveal Narrow Reveal	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	36% 38% 38%
1344-IOF-1	48 × 48 × 1	Trim Reveal Narrow Reveal	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	36% 38% 38%
1362-IOF-1	24 x 24 x 1-1/2	Trim Reveal Narrow Reveal	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	38% 40% 40%
1360-IOF-1	24 x 48 x 1-1/2	Trim Reveal Narrow Reveal	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	38% 40% 40%
1366-IOF-1	24 x 96 x 1-1/2	Trim	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	38%
1364-IOF-1	48 x 48 x 1-1/2	Trim Reveal Narrow Reveal	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	38% 40% 40%

With optional foil backing

CAN'T FIND A SIZE? Contact your local Sales Representative 1-800-233-8990

# PHYSICAL DATA

#### MATERIAL

Fiberglass Ceilings

# ASTM E1264 CLASSIFICATION

Type XII, Form 2, Pattern E

# FIRE PERFORMANCE Per ASTM E1264: Class A, Flame Spread 25 or less

Per ASTM E1264: Class A, Flame Spread 25 or less Per ASTM E84: Smoke Developed 50 or less

#### MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

#### VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010.

#### MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment. Cleanable with sanitizing chemicals.

#### WARRANTY

10 year 104/95 Limited Warranty





# ATTRIBUTES - METRIC SIZES

ITEM NUMBER	DIMENSIONS (INCHES)	EDGE DETAIL	NRC	© CAC	SAG RESISTANT	MOLD RESISTANT	LR	WASHABLE	SCRATCH RESISTANT	FIRE RATING	LOW VOC EMISSIONS	RECYCLED CONTENT
1322M-IOF-1	600 x 600 x 19	Trim	0.90	22	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	34%
1320M-IOF-1	600 x 1200 x 19	Trim	0.90	24	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	34%
1347M-IOF-1	500 x 1500 x 25	Trim Reveal Narrow Reveal	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	36% 38% 38%
1342M-IOF-1	600 x 600 x 25	Trim Reveal Narrow Reveal	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	36% 38% 38%
1340M-IOF-1	600 x 1200 x 25	Trim Reveal Narrow Reveal	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	36% 38% 38%
1341M-IOF-1	600 x 1500 x 25	Trim Reveal Narrow Reveal	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	36% 38% 38%
1343M-IOF-1	750 × 750 × 25	Trim Reveal Narrow Reveal	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	36% 38% 38%
1349M-IOF-1	750 x 1500 x 25	Trim Reveal Narrow Reveal	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	36% 38% 38%
1344M-IOF-1	1200 x 1200 x 25	Trim Reveal Narrow Reveal	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	36% 38% 38%
1362M-IOF-1	600 x 600 x 38	Trim Reveal Narrow Reveal	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	38% 40% 40%
1360M-IOF-1	600 x 1200 x 38	Trim Reveal Narrow Reveal	0.95	25	Yes	Inherent	0.90	Yes	Yes	Class A	Certified	38% 40% 40%

With optional foil backing

CAN'T FIND A SIZE? Contact your local Sales Representative 1-800-233-8990

\*Ordering Procedure: To order preferences for edge details, select the item number above, then add the appropriate Edge Detail Code below. Example:

Item Number	Edge Detail Code (Other than Trim)						
Select from chart	B represents Reveal (15/16") F represents Narrow Reveal (9/16")						
Example: 1342-IOF-1	1342 <b>B</b> -IOF-1 1342 <b>MB</b> -IOF-1						

# PHYSICAL DATA

#### MATERIAL

Fiberglass Ceilings

# ASTM E1264 CLASSIFICATION

Type XII, Form 2, Pattern E

FIRE PERFORMANCE
Per ASTM E1264: Class A, Flame Spread 25 or less
Per ASTM E84: Smoke Developed 50 or less

# MOLD/MILDEW RESISTANCE

Fiberglass substrate is inherently resistant to the growth of mold and mildew.

#### VOC EMISSIONS

Independently certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010.

# MAINTENANCE

Wipe with a soft cloth or vacuum with brush attachment. Cleanable with sanitizing chemicals.

#### WARRANTY

10 year 104/95 Limited Warranty

